

AN EXPERIMENTAL ANALYSIS OF DIRECT EVAPORATIVE COOLER BY VARYING MATERIALS OF COOLING PAD

KAPISH T DHAKULKAR¹, M. R. DHARME² & K. R. GAWANDE³

¹M. E. Scholar, DRGIT&R, Amravati, India

²Associate Professor, DRGIT&R, Amravati, India

³Assistant Professor, DRGIT&R, Amravati, India

ABSTRACT

This research aims to examine the performance of the direct evaporative cooler, by using the cooling pads of different materials. The efficiency of direct evaporative cooler mostly depends on the cooling pad and hence, the material used in the cooling pad plays a very vital role. Here, the performance of direct evaporative cooler is analyzed by using cooling pads of four different materials such as cellulose paper pad, wood fibers, wood wool (Aspen) and coconut fibres. Apart from these four types of cooling pads, also the performance of direct evaporative cooler is analyzed by using three different types of cooling pads simultaneously on three sides of the cooler, which mainly includes cellulose paper pad, coconut fibre pad and wood wool (Aspen) pad. Two most important terms considered in this analysis are temperature and humidity. The readings of these two terms are taken for each type of cooling pad and also, the further calculations are done based on these readings. Comparison of results for various types of cooling pad is also done. The paper rounds off with conclusions and an agenda for future research in this area.

KEYWORDS: *Evaporative, Humidity, Temperature, Pad, Cooler & Analysis*

Received: Nov 06, 2017; **Accepted:** Nov 25, 2017; **Published:** Dec 07, 2017; **Paper Id.:** IJMPERDDEC201766

INTRODUCTION

Direct evaporative cooling (DEC) uses evaporating water, combined with a wetted medium to cool the temperature of air as it passes through. Heat is removed from the surrounding air in the vaporization of the water by passing through or around a wetted surface. The air is cooled in the process and the humidity is increased. Unfortunately, evaporative cooling requires an abundant water source and is only effective when the relative humidity is low, restricting its efficient use to dry climates. The air supplied by the evaporative cooler is nearly 100% humid. Very humid air prevents the evaporative cooling of sweaty or wet skin. High humidity in air accelerates corrosion. This can considerably shorten the life of electronic equipment. High humidity in the air may cause condensation (which can be extremely hazardous, if it happens inside electrical equipment). Cooled air may bring dust and pollen into the space, causing discomfort for allergy sufferers. Growth of microorganisms such as molds on the cooler pads may cause allergy problems in sensitive individuals, as evaporative coolers use on-site water.





Figure.1: Direct Evaporative Cooling System

COOLING PADS

Cooling pads have a very high impact on the performance of a direct evaporative cooler. Cooling efficiency and humidity are the two important factors to be considered while analyzing the performance of an direct evaporative cooler. These two factors, mostly depend upon the type of cooling pad used. Now a days, cooling pads of materials such as Aspen wood wool, wood fibers and cellulose paper pad are being used in the direct evaporative coolers. Though these pads are giving a good cooling efficiency, but they also increase the humidity. So, this increased humidity is the major problem today in case of these direct evaporative coolers. Researchers from all over the world are trying to search or develop new, efficient and sustainable pad materials which is very much required for further enhancing cooling potential of evaporative cooling devices. In the present work, one new cooling pad material, i.e. Coconut fiber has been tested. The views of the various types of cooling pad materials used in this work are given in the following figures.




Figure 2: Wood Fibers



Aspenwood fiber pad

Figure 3: Aspen Wood Wool



Paper cellulose pad

Figure 4: Cellulose Paper Pad



Figure 5: Coconut Fibers

EXPERIMENTAL ANALYSIS

The cooling pads of all the above four types of materials were prepared and tested experimentally one by one in a prepared model of a direct evaporative cooler. Apart from these four types of cooling pads, also the model of a direct evaporative cooler has been tested by using three different types of cooling pads on its three different sides and they include cellulose paper pad, Aspen wood wool pad and Coconut fiber pad. In this way, five times experimentations were performed by varying the cooling pads and the readings of temperature and humidity were taken. The comparison between the readings of various types of cooling pad is given in the following table.

Table 1: Experimental Readings

Sr. No.	Cooling Pad Material	Inlet Dry Bulb Temperature ($^{\circ}\text{C}$)	Humidity (%) Before Cooling	Outlet Dry Bulb Temperature ($^{\circ}\text{C}$)	Humidity (%) After Cooling
1	Wood fibers	28	56	25	70
2	Aspen wood wool	28	57	23	73
3	Cellulose paper pad	30	55	22	72
4	Coconut fibers	27	59	24	68
5	Cellulose, Aspen & Coconut fibers mixture	28	60	22	68

Based on the above readings, the efficiency of an direct evaporative cooler can be calculated as given below.

Considering wood fibers as a cooling pad material.

From the psychometric chart,

For DBT = 28°C and Humidity = 56%,

We get Wet bulb temperature(WBT) = 19°C

Now, cooling efficiency is given by,

$$\text{Cooling efficiency} = [(t_1 - t_2) / (t_1 - t_s)] * 100$$

Where, t_1 =Inlet DBT, t_2 =outlet DBT, t_s =WBT

Therefore, from the above the cooling efficiency for wood fibers is 33.33%

In the similar way, the cooling efficiency for other cooling pad materials can be found.

RESULTS

The comparison of results of the cooling efficiency for various types of cooling pads is shown in the following

table.

Table 2: Comparison of Cooling Efficiency

Sr. No.	Cooling Pad Material	Cooling Efficiency (%)
1	Wood fibers	33.33
2	Aspen wood wool	55.85
3	Cellulose paper pad	80
4	Coconut fibers	33.33
5	Cellulose, Aspen & Coconut fibers mixture	66.66

CONCLUSIONS

- An experimental analysis of an direct evaporative cooler by varying materials of cooling pads have been performed.
- From the analysis it is found that Cellulose paper pads and Aspen wood wool pads provides good cooling but they increases the humidity very highly and Coconut fiber pads has least humidity.
- So, a mixute of these three cooling pads i.e. Cellulose paper pad, Aspen wood wool and Coconut fibres is prepared and it is seen from the experiment that this mixture provides a good cooling effect and also has a least humidity.

REFERENCES

1. Chenguang Sheng, A.G. Agwu Nnanna, "Empirical correlation of cooling efficiency and transport phenomena of direct evaporative cooler", *Science Direct, Applied Thermal Engineering* 40 (2012) 48-55.
2. Viswa Mohan Pedagogu, *Modelling, Manufacturing of Mold Tool and Plastic Flow Analysis of an Air Cooler Tank, International Journal of Mechanical and Production Engineering Research and Development (IJMPERD), Volume 3, Issue 3, July - August 2013, pp. 109-116*
3. Zhuo Xianrong, Chen Shu, "Enthalpy Transfer Analysis & Calculation about Heat and Moisture Exchanger Process during Air Flowing on Water-film Channel of Cooling Pad", *2011 International Conference on Computer Distributed Control and Intelligent Environmental Monitoring, IEEE*.
4. Mohammad Ul Hassan & Sudarshan Singh, *Fabrication, Experimentation, Performance Evaluation of Two Stage Air Cooler and Comparison with Conventional Air Cooler, International Journal of Mechanical Engineering (IJME), Volume 5, Issue 4, Jun - Jul 2016, pp. 75-84*
5. K.Senthilkumar, PSS.Srinivasan, "Application of Taguchi Method for the Optimization of System Parameters of Centrifugal Evaporative Air Cooler", *Journal of Thermal Science Vol.19, No.5 (2010) 473-479*.
6. J.M. Wu, X. Huang, H. Zhang, "Theoretical analysis on heat and mass transfer in a direct evaporative cooler", *Science Direct, Applied Thermal Engineering* 29 (2009) 980-984.
7. J.K. Jain, D.A. Hindoliya, "Experimental performance of new evaporative cooling pad materials", *Science Direct Sustainable Cities and Society* 1 (2011) 252- 256.
8. Hossein Lotfizadeh, Mohammad Layeghi, "Design and performance analysis of a small solar evaporative cooler" *Springer Science+Business Media Dordrecht 2013, Energy Efficiency (2014) 7:55-64*.

9. J. K. Jain, D. A. Hindoliya, "Correlations for Saturation Efficiency of Evaporative Cooling Pads", *J. Inst. Eng. India Ser. C* (January–March 2014) 95(1):5–10.
10. V. V. Birangane, A. M. Patil, "Comparison of Air Cooled and Evaporatively Cooled Refrigeration Systems – A Review Paper", *Int. Journal of Engineering Research and Applications*, ISSN : 2248-9622, Vol. 4, Issue 6(Version 2), June 2014, pp.208-211.
11. E. Velasco Gómez, F.C. Rey Martínez, A. Tejero González, "The phenomenon of evaporative cooling from a humid surface as an alternative method for air-conditioning", *International Journal of Energy and Environment*, Volume 1, Issue 1, 2010 pp.69-96.
12. Md. Almostasim Mahmud, Dr. Md. Alamgir Hossain, M. A. Muktedir, "Design optimisation and installation of the evaporative cooler in the perspective of Bangladesh", *International Journal of Emerging Technology and Advanced Engineering*, ISSN 2250-2459, Volume 2, Issue 11, November 2012.
13. J.T. Liberty, B.O. Ugwuishiwu, S.A Pukuma and C.E Odo, "Principles and Application of Evaporative Cooling Systems for Fruits and Vegetables Preservation", *International Journal of Current Engineering and Technology*, ISSN 2277 – 4106, Vol.3, No.3 (August 2013).
14. Claudio Cianfrini, Massimo Corcione, Emanuele Habib, Alessandro Quintino, "Energy performance of air-conditioning systems using an indirect evaporative cooling combined with a cooling/reheating treatment", *Science Direct, Energy and Buildings* 69 (2014) 490–497.
15. Min-Hwi Kim, Joon-Young Park, Min-Ki Sung, An-Seop Choi, Jae-Weon Jeong, "Annual operating energy savings of liquid desiccant and evaporative-cooling-assisted 100% outdoor air system", *Science Direct, Energy and Buildings* 76 (2014) 538–550.
16. Tianwei Wang, Chenguang Sheng, A.G. Agwu Nnanna, "Experimental investigation of air conditioning system using evaporative cooling condenser", *Science Direct, Energy and Buildings* 81 (2014) 435–443.
17. WU Zhijiang, WANG Nan, ZHU Gongsheng, "Application Research of Evaporative Cooling in the Waste Heat Recovery", *2010 International Conference on Digital Manufacturing & Automation, IEEE*.

